






Fast assembly concealed hinge with integrated Silent System

- ▶ Sensys 8631i for thick doors
- ▶ Opening angle 95°



- ▶ Concealed hinge with clip on installation and integrated Silent System
- ▶ Quality classification under EN 15570, Level 2
- ▶ For door thickness of 15 – 32 mm
- ▶ Cup diameter 35 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated overlay adjustment + 2 mm / - 2 mm
- ▶ Integrated depth adjustment + 3 mm / - 2 mm
- ▶ Height adjustment at mounting plate
- ▶ Hinge arm material: steel nickel plated
- ▶ Hinge cup material: steel nickel plated

Sensys 8631i, opening angle 95°

Cup assembly	Drilling pattern	Mounting drilling ø x T mm	full overlay	half overlay	inset	PU
						
For screwing on TH 52		-	9 091 400	9 091 410	9 091 420	1/50 ea.
For pressing in TH 53		ø 10 x 11	9 091 401	9 091 411	9 091 421	1/50 ea.
Flash fast assembly TH 54		ø 10 x 11	9 091 402	9 091 412	9 091 422	1/50 ea.
For screwing on TB 52		-	9 091 430	9 091 440	9 091 450	1/50 ea.
For pressing in TB 53		ø 8 x 11	9 091 431	9 091 441	9 091 451	1/50 ea.
Flash fast assembly TB 54		ø 8 x 11	9 091 432	9 091 442	9 091 452	1/50 ea.