


- ▶ Rastex 15
- ▶ Twister dowel for Rastex 15


## Twister screw in dowel DU 243 T / DU 232 T



- ▶ With direct fixing thread for drilling diameter of 5 mm
- ▶ Dowel length 20 / 30 mm
- ▶ DU 232 T can also be used for VB Insert for lightweight panels with 8 mm face layers
- ▶ For lightweight panels with 4 mm face layers installation only with Hettinject bonding dowels
- ▶ Steel / green or black plastic
- ▶ Can be used in System 32

Article version	Dowel length mm	Order no.	PU
Twister DU 243 T, galvanised	20	<b>0 020 056</b>	1/200 ea.
Twister DU 232 T, galvanised	30	<b>0 020 058</b>	1/200 ea.

## Twister screw in dowel DU 644 T




- ▶ M6 x 7.8 mm thread
- ▶ Dowel length 30 mm
- ▶ Steel / black plastic

Advice:

- ▶ Please order M6 sockets separately, see page 820 - 821

Article version	Order no.	PU
Twister DU 644 T, galvanised	<b>0 020 157</b>	1/200 ea.

## Screw in dowel DU 425 / DU 428



- ▶ M4 x 7.8 mm thread
- ▶ Dowel length 20 / 30 mm
- ▶ Steel
- ▶ Can be used in System 32

Advice:

- ▶ Please order M4 sockets separately, see page 820 - 821

Article version	Dowel length mm	Order no.	PU
DU 428 bright	20	<b>0 079 523</b>	1/200 ea.
DU 425 bright	30	<b>0 079 521</b>	1/200 ea.